

Superlock



For SC/GZ Guy Strands



The range of superlock fittings have been designed as an easy and efficient way of terminating stays back onto themselves in pole-top applications. The finished application has a clean low profile, ensuring a very high quality final assembly.

The superlock range has the same full-rated strength of the stay wire and has been proven to operate under all conditions including high impact motor vehicle collisions. They;

- will not deteriorate
- replace cumbersome bolted methods
- are high strength and impact resistant
- are quickly and easily applied
- are neat and cleanly finished

Part Number	Conductor Stranding	Conductor Diameter (mm)	Standard Pack Quantity	Colour Code
GSC-055	3/2.75	5.91	75	White
GSC-060	7/2.00	6.00	20	Yellow
GSC-075	7/2.50	7.50	30	Blue
GSC-083	7/2.75	8.25	20	White
GSC-100	7/3.25 19/2.00	10.00	20	Orange/Yellow
GSC-113	7/3.75	11.25	15	Black
GSC-120	7/4.00	12.00	10	Brown
GSC-138	19/2.75	13.75	10	White
GSC-163	19/3.25	16.25	10	Orange

SAFETY CONSIDERATIONS

- This product is intended for a single (one-time) use and for the specified application, although it may be re-applied twice for retensioning within 90 days from initial installation.
- Do not modify this product in any way.
- This product is intended for use by qualified linesmen only.
- When working in the area of energised line with this product, extra care should be taken to prevent accidental electrical contact.
- For proper performance and personal safety, be sure to select the proper size PREFORMED™ products before application.
- PREFORMED™ products are precision devices. To ensure proper performance, they should be stored in cartons under cover and handled carefully.