



For Steel Conductor SC/GZ



Note: Add part number AS-54-17 or AS-54-22 if sheave is required.

Standard part numbers (-54) are designed to suit 54mm sheaves. Contact PLP for other sizes.

Preformed Twin-Grips are designed for SC/GZ for earth wire utilising the PLP aluminium sheave. The fitting is used at support positions and is designed to provide superior mechanical strength and resilience during conductor motion.

- Easy application
- Long life
- Positive grip

Part Number	Conductor Stranding	Conductor Diameter (mm)	Standard Pack Quantity	Colour Code
GTG-043-54	3/2.00	4.25	10	Yellow
GTG-048-54	7/1.60	4.80	10	Green
GTG-060-54	7/2.00	6.00	25	White
GTG-075-54	7/2.50	7.50	15	Blue
GTG-083-54	7/2.75	8.25	15	White
GTG-100-54	19/2.00 7/3.25	10.00 9.75	12	Yellow Orange
GTG-113-54	7/4.50	13.50	8	Green
GTG-138-54	19/2.75	13.75	10	White

For Aluminium Conductor



Note: Add part number AS-54-17 or AS-54-22 if sheave is required.

Standard part numbers (-54) are designed to suit 54mm sheaves. Contact PLP for other sizes.

Preformed Twin-Grips are designed to support ACSR and SC/AC utilising the PLP Aluminium Sheave. The fitting is designed to be used where a high level of mechanical strength is required. It provides resilience during conductor motion and unbalanced loads.

- Easy application.
- Long life.
- Positive grip.
- Filler rods can be supplied to allow a bond clamp to be Attached for earthwire applications.

Part Number	Conductor Stranding	Conductor Diameter (mm)	Standard Pack Quantity	Colour Code
AWTG-075-54	7/2.50	7.50	10	Blue
AWTG-083-54	7/2.75	8.25	10	White
AWTG-101-54	7/3.35	10.05	10	Orange
AWTG-113-54	7/3.75	11.25	10	Black
AWTG-135-54	7/4.50	13.50	8	Green
AWTG-163-54	19/3.25	16.25	6	Orange