


Spiral Vibration Dampers



Spiral Vibration Dampers



Made from high impact, UV resistant, polyvinyl chloride (PVC), they are non-corrosive and do not abrade the conductor or require engineering calculations for positioning. Vibration dampers are designed to reduce cable vibration at tangent supports and deadend positions. The degree of protection needed on a specific line depends upon a number of factors such as line design, temperature, tension and exposure to the wind flow. Please make PLP aware of any previous vibration problems or concerns in the area.

Part Number	Conductor Diameter Range (mm)	Standard Pack Quantity	Colour Code
SVD-0102	4.42 - 6.34	30	Red
SVD-0103	6.35 - 8.29	60	Blue
SVD-0104	8.30 - 11.74	60	Black
SVD-0105	11.75 - 14.30	60	Yellow
SVD-0106	14.31 - 19.30	25	Green

SPIRAL VIBRATION DAMPER PLACEMENT GUIDE

Span Length (m)	Standard SVD Quantities
0 - 244	2
245 - 488	4
489 - 732	6
733 - 976	8
977 - 1220	10

1. SVDs may be subset together in sets of up to 3 apiece; do not place more than 3 SVDs together in a subset as this can cause them to bind and reduce their overall effectiveness.
2. SVDs have the advantage of being placement independent and may be placed at either end of the span, or on both ends if so desired. However, please note that SVDs are designed to be placed directly on to the conductor or shield wire and not on to rods or attachment hardware. A general recommendation, place SVDs on the bare conductor or shield wire approximately one hand's width away from suspension rods, dead-end rods, ties, etc.
3. Please consult PLP for recommendations when;
 - * Flat open Terrain, river or gully crossings
 - * Tensions are greater than 20% UTS
 - * Aerial warning spheres are installed